

AWX2000C

Construction grade negative air portable air cleaner and filtration system with the performance of full sized negative air units but is easy to move and set up. Used in mold, asbestos, and lead abatement projects.



DIMENSIONS WxLxH with wheels: 20" x 34" x 29"

WEIGHT with FILTERS (lbs): 125

SHIP WT (lbs): 145

AIRFLOW (cfm): Two Speeds: 1000 & 1800

VARIABLE SPEED: No

POWER/MAX CONSUMPTION: 115 VAC/ 50-60Hz 12.0 amps

FILTERS: HEPA 99.97% @0.3µ with particle board frame. Primary/secondary dual-ply Dustlok® polyester pad filter.

OPTIONAL FILTERS: HEPA 99.99% @0.3µ with metal frame. OdorGuard600 activated carbon filter pad or carbon/alumina fiber filter for odor control/toxic fumes. HEPA filter can be replaced with a 95% ASHRAE bag filter. Collects bulk dust from concrete, wood and plaster cutting/grinding operations.

FILTRATION STAGES: 3 to 4

UV: NA

HOUSING: Galvanized steel with closed end rivet construction. All seams are silicon sealed before riveting. Carrying handles have rubber grips. Four (4) 5" casters with reinforced mounting channels. Two (2) are fixed, two (2) swivel.

CONTROLS: Recessed control panel with two-speed rocker switch. "Change Filter" LED indicator light

EXHAUST/INTAKE (Inches): 12

CORD LENGTH (FT): 6



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD C22.2
NO. 113-M1984

AIRWORKX® has the perfect Air Filtration System solution. Ask us about our other 'Workx™ family products. Call for pricing and lease-to-own programs.



Making Air Work For You
Phone: 1-855-668-8400
Fax: 1-855-668-8401
E-mail: info@airworkx.com
Website: www.airworkx.com