

AWX2200UL

Full-sized two-speed portable negative air scrubber for use in abatement, construction and remediation projects and any applications where HEPA filtration is required.



DIMENSIONS WxLxH with wheels: 26" x 34" x 31"

WEIGHT with FILTERS (lbs): 125

SHIP WT (lbs): 160

AIRFLOW (cfm): Two Speeds: 1000 and 2000

VARIABLE SPEED: No

POWER/MAX CONSUMPTION: 115 VAC/ 50-60Hz 13.8 amps

FILTERS: HEPA 99.97% @0.3µ with particle board frame. Primary/secondary dual-ply Dustlok® polyester pad filter.

OPTIONAL FILTERS: Disposable activated carbon V-bank filter with 36 lbs of carbon, carbon/alumina fiber filter, 95% ASHRAE bag filter with 8-pockets (24" x 24" x 12"). Collects bulk dust from concrete, wood and plaster cutting/grinding operations.

FILTRATION STAGES: 3 to 5

UV: NA

HOUSING: Aluminum and Galvanized steel with epoxy paint. Carrying handles with rubber grips. Four (4) 5" casters with reinforced mounting channels. Two (2) are fixed, two (2) swivel.

CONTROLS: Recessed control panel with two-speed rocker switch. Differential pressure gauge (0-5" W.C.) to indicate HEPA filter loading.

EXHAUST/INTAKE (Inches): 12

CORD LENGTH (FT): 1 ft. pigtail



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD C22.2
NO. 113-M1984

AIRWORKX® has the perfect Air Filtration System solution. Ask us about our other 'Workx™ family products. Call for pricing and lease-to-own programs.



Making Air Work For You

Phone: 1-855-668-8400

Fax: 1-855-668-8401

E-mail: info@airworkx.com

Website: www.airworkx.com