

AWX1200PAC

Midsize variable speed portable air cleaner with small footprint. Designed for use in hospital and other medical environments. Helps remove biological and chemical contaminants and particulates. Quiet operation with fully variable airflow. Can be used to provide either a positive or negative pressure environment or as a recirculation device.



DIMENSIONS WxLxH with wheels: 22" x 19" x 42"

WEIGHT with FILTERS (lbs): 115

SHIP WT (lbs): 125

AIRFLOW (cfm): 200-1100

VARIABLE SPEED: Yes

POWER / MAX CONSUMPTION: Standard: 115 VAC/ 50-60Hz 6.0 amps Optional: 230 VAC/50-60 Hz

FILTERS: HEPA 99.99% @0.3 μ with metal frame. Primary/Secondary Filter - Pleated MERV-11 rated Inlet has 16"x16" pleated filter and protective screen. Discharge on top through HEPA and protective screen.

OPTIONAL FILTERS: HEPA 99.99% @0.1-0.2 μ with metal frame. Activated carbon or carbon/alumina fiber pad for odor control/toxic fumes.

FILTRATION STAGES: 3 to 4

UV: UV-C germicidal light module with four (4) straight 12" UV-C lights with on/off switch

HOUSING: Aluminum, silicon-sealed before riveting. Galvanized reinforcements. Molded polyurethane push handle. Four (4) 3" swivel casters.

CONTROLS: Recessed panel with Variable Speed Control. Differential pressure gauge (0-3" W.C.) to indicate HEPA filter loading. Hour meter with LCD display. ON/OFF switch for UVGI lights and LED status lights for lamps/ballast.

EXHAUST/INTAKE (Inches): 10 (requires optional connection adapter)

CORD LENGTH (FT): 6



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD C22.2
NO. 113-M1984

AIRWORKX[®] has the perfect Air Filtration System solution. Ask us about our other 'Workx[™]' family products. Call for pricing and lease-to-own programs.



Proudly Made in USA

© 2012 AIRWORKX RV11-12



Making Air Work For You
Phone: 1-855-668-8400
Fax: 1-855-668-8401
E-mail: info@airworkx.com
Website: www.airworkx.com