

AWX1200V

Upright, compact, negative air scrubber for mold, asbestos and lead dust abatement. Operates horizontally as well as vertically. Available accessories for removing chemical fumes and biological contaminants.



DIMENSIONS WxLxH with wheels: 24" x 25" x 38"

WEIGHT with FILTERS (lbs): 105

SHIP WT (lbs): 125

AIRFLOW (cfm): 150-1100

VARIABLE SPEED: Yes

POWER/MAX CONSUMPTION: 115 VAC/ 50-60Hz 6.0 amps

FILTERS: HEPA 99.97% @0.3 μ with particle board frame. Primary/secondary dual-ply Dustlok® polyester pad filter.

OPTIONAL FILTERS: HEPA 99.99% @0.3 μ with metal frame. OdorGuard 600 activated carbon filter pad or carbon/alumina fiber filter for odor control/toxic fumes.

FILTRATION STAGES: 3 to 5

UV: Optional UV-C/V germicidal light modules with two (2) or four (4) 12" straight UV-C lights.

HOUSING: Aluminum, silicon-sealed before riveting. Molded polyurethane handle. Two (2) 10" wheels with heavy duty axle assembly. Two (2) 3" swivel casters

CONTROLS: Recessed control panel with Variable Speed Control. Differential pressure gauge (0-3" W.C.) indicates HEPA filter loading status.

EXHAUST/INTAKE (Inches): 10

CORD LENGTH (FT): 6



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD C22.2
NO. 113-M1984

AIRWORKX® has the perfect Air Filtration System solution. Ask us about our other 'Workx™ family products. Call for pricing and lease-to-own programs.



Making Air Work For You

Phone: 1-855-668-8400

Fax: 1-855-668-8401

E-mail: info@airworkx.com

Website: www.airworkx.com