

# AWX1300V

*Narrow profile negative air machine used in mold, asbestos, and lead abatement projects. Available accessories for removing chemical fumes and biological contaminants. Helps provide a cleaner and healthier environment in industrial facilities as well as in abatement projects.*



**DIMENSIONS WxLxH with wheels:** 14" x 33" x 29"

**WEIGHT with FILTERS (lbs):** 90

**SHIP WT (lbs):** 101

**AIRFLOW (cfm):** 300-1250

**VARIABLE SPEED:** Yes

**POWER/MAX CONSUMPTION:** 115 VAC/ 50-60Hz 8.7 amps

**FILTERS:** HEPA 99.97% @0.3µ with particle board frame. Primary/secondary dual-ply Dustlok® polyester pad filters.

**OPTIONAL FILTERS:** HEPA 99.99% @0.3µ with metal frame. Activated carbon filter pad for odor control/toxic fumes.

**FILTRATION STAGES:** 3 to 4

**UV:** NA

**HOUSING:** Aluminum with closed-end rivet construction, silicon-sealed before riveting. Four (4) 3" swivel casters.

**CONTROLS:** Recessed control panel with Variable Speed Control. Differential pressure gauge (0-3" W.C.) indicates HEPA filter loading status.

**EXHAUST/INTAKE (Inches):** 10

**CORD LENGTH (FT):** 6



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD C22.2  
NO. 113-M1984

**AIRWORKX®** has the perfect Air Filtration System solution. Ask us about our other 'Workx™' family products. Call for pricing and lease-to-own programs.



Proudly Made in USA

© 2012 AIRWORKX RV11-12



**Making Air Work For You**

**Phone:** 1-855-668-8400

**Fax:** 1-855-668-8401

**E-mail:** [info@airworkx.com](mailto:info@airworkx.com)

**Website:** [www.airworkx.com](http://www.airworkx.com)