

AWX600N

Lighter weight, medium-duty portable negative air cleaning and filtration system for mold, asbestos and lead abatement projects. Operates stacked 3 high. Daisy-chain up to 5 units. 58-68 dBA at 3'. Soft rubber grip carrying handle. GFI protected convenience outlets with 12 amp circuit breaker.



DIMENSIONS WxLxH: 18.5" x 25" x 18.5"

WEIGHT with FILTERS (lbs): 40

SHIP WT (lbs): 60

AIRFLOW (cfm): 200-600

VARIABLE SPEED: Yes

POWER/MAX CONSUMPTION: 115 VAC/ 50-60Hz 2.2 amps

FILTERS: HEPA filters are particle board framed 99.97% efficiency @ 0.3µ. Primary/secondary dual-ply Dustlok® polyester pad filters.

OPTIONAL FILTERS: Geo95 MERV 14 Filter.
OdorGuard 600 carbon filter

FILTRATION STAGES: 3 to 4

UV: NA

HOUSING: Flame Retardant Polyethylene

CONTROLS: Variable Speed Controller. Change Filter Indicator Light. Convenience GFI protected outlet with 12 amp breaker.

EXHAUST/INTAKE (Inches): 10

CORD LENGTH (FT): 6



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD C22.2
NO. 113-M1984

AIRWORKX® has the perfect Air Filtration System solution. Ask us about our other 'Workx™' family products. Call for pricing and lease-to-own programs.



Proudly Made in USA

© 2012 AIRWORKX RV11-12



Making Air Work For You
Phone: 1-855-668-8400
Fax: 1-855-668-8401
E-mail: info@airworkx.com
Website: www.airworkx.com