

AWX600V

Lightweight portable negative air machine for mold, asbestos and lead abatement projects. Available with optional UV germicidal light modules and activated carbon filters for removing VOCs and biological contaminants.



DIMENSIONS WxLxH with wheels: 14" x 30.5" x 18.5"

WEIGHT with FILTERS (lbs): 55

SHIP WT (lbs): 70

AIRFLOW (cfm): 150-600

VARIABLE SPEED: Yes

POWER/MAX CONSUMPTION: 115 VAC/ 50-60Hz 3.5 amps

FILTERS: HEPA 99.97% @0.3 μ with particle board frame.
Primary/secondary dual-ply Dustlok[®] polyester pad filter.

OPTIONAL FILTERS: HEPA 99.99% @0.3 μ with metal frame.
Activated carbon filter for odor control/toxic fumes.

FILTRATION STAGES: 3 to 4

UV: Optional UV-C/V germicidal light modules with two (2) or four (4) 12" straight UV-C lights.

HOUSING: Aluminum, silicon-sealed before riveting. Four (4) 3" swivel casters. Two carrying handles with rubber grips.

CONTROLS: Variable Speed Controller. Differential pressure gauge (0-3" W.C.) indicates HEPA filter loading status.

EXHAUST/INTAKE (Inches): 8

CORD LENGTH (FT): 6



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD C22.2
NO. 113-M1984

AIRWORKX[®] has the perfect Air Filtration System solution. Ask us about our other 'Workx[™] family products. Call for pricing and lease-to-own programs.



Making Air Work For You
Phone: 1-855-668-8400
Fax: 1-855-668-8401
E-mail: info@airworkx.com
Website: www.airworkx.com